

NSL-MH10 Standard Chain Bag

NAV ID - I0068846

CODE - NSL10MHCBM

Chain Blocks Chain Bags are bucket type bags for upright or inverted hand chain hoist use. They are held by one high resistance polyester strap which takes the weight of the chain and distributes it over the upper metal frame. Spring loaded safety clip CE compliant and snap hook. Bucket opening and chain bag capacity allows to fit load chain and hand chain, leaving enough space to put the chain block inside of the chain bag, for simple and easy transportation or storage.

- CHAIN BAG CAPACITY = 12m Load Chain + 11m Hand Chain @ 60%

BELT TECH DATA:

- Polypropylene 5cm belt
- 25-27% elongation value
- 240 filaments
- 1100 kg Minimum Breaking Point
- 175 ° Celsius melting point

FABRIC TECH DATA:

- 840 Nylon PVC Coated
- 28-31% elongation value
- Test UNI ISO 13934-1:200
- N 502 medium breaking load value
- Test UNI 4818:1992 p.te 9

MEASUREMENTS:

- Opening = 20cm diameter
- Length = 40cm
- Weight = 0.71 Kg
- SWL = 18Kg - 40lbs

BAG LABEL:



NEXT StageLIFT

Chain bag NSL-MH10

SWL: 18 kg (40 lbs)
@ 8:1 safety factor

Maximum capacity
6 x 18 mm loadchain: 10 m (33 ft) @50%
3.5 x 16 mm handchain: 10 m (33 ft) @50%
+1x 1000 kg handchain block

www.NEXT-truss.com

